

Beam Clamps

Load Rated

IPBKZ



The IPBKZ beam clamp is used for lifting, transfer and stacking of I-Beams. An over-center hoist eye allows for the beam flange to remain vertical. This series of clamps can be used in the vertical and horizontal moving, transfer and stacking of different types of structural designs, such as I-Beams, angles, etc, depending on the application desired.


For the Transfer and Stacking of Steel Beams

- Available in capacities of .75 thru 3.75 metric tons.
- Wide variety of jaw openings available: 0 to 28mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- Company name (IP), logo, Working Load Limit and jaw opening permanently stamped on body.
- Each product is individually serialized, with the serial number and Proof Load test date stamped on body. Serial number is included on the test certificate with maintenance and warranty logbook.
- Optional IP-5000 Stinger assembly available (see page 382). Allows for easy connection between the clamp and hoist hook.
- Minimum WLL of 10% of Maximum WLL.
- Maintenance replacement parts are available.
- Manufactured by a ISO 9001 facility.
- All sizes are **RFID EQUIPPED**.

IPVUZ




The IPVZ / IPVUZ beam clamp is used for vertical lift and transfer of angle iron and other loads that have only a small gripping area for the clamp ("U" has universal hoisting eye). This series of clamps can be used in the vertical and horizontal moving, transfer and stacking of different types of structural designs, such as I-Beams, H-beams, angles, etc, depending on the application desired.



Model IPBKZ

Model	Working Load Limit (t)*	IPBKZ Stock No.	Weight Each (kg.)	Dimensions (mm)								
				Jaw A	B	C	D	E	F	G	H	J
IPBKZ	0.75	2705780	3.5	5 - 15	43	132	192	45	113	47	38	10
IPBKZ	1.5	2705781	7.0	5 - 25	62	210	300	70	163	61	50	16
IPBKZ	3.75	2705782	15.5	5 - 28	75	260	415	100	202	78	52	20

* Design Factor based on EN 13155 and ASME B30.20.



Model IPVUZ: Universal Hoisting Eye

Model IPVZ : Fixed Hoisting Eye

Model	Working Load Limit (t)*	Stock No.	Weight Each (kg.)	Dimensions (mm)									
				Jaw A	B	C	D	E	F	G	H	J	K
IPVUZ	0.75	2705146	2.3	0 - 15	45	138	238	30	128	41	37	-	10
IPVUZ	1.5	2705147	8.9	0 - 20	78	201	378	70	200	61	72	-	16
Fixed Hoisting Eye													
IPVZ	0.75	2705096	2.1	0 - 15	26	128	207	30	115	41	30	-	10
IPVZ	1.5	2705097	6.2	0 - 20	60	200	339	70	180	52	50	-	16

* Design Factor based on EN 13155 and ASME B30.20.